


- **HS No.:** 2921 3099
- **Appearance:** Blendcat DMCHA 50 is a clear, colorless flammable mixture of DMCHA and DEG in the ratio 50:50.



## SPECIFICATIONS

| Parameter                         | Ingredient 1                       | Ingredient 2                |
|-----------------------------------|------------------------------------|-----------------------------|
| <b>Chemical name:</b>             | <b>N,N-Dimethylcyclohexylamine</b> | <b>2,2'-Oxydiethan-1-ol</b> |
| <b>Index number:</b>              | -                                  | 603-140-00-6                |
| <b>EC No.:</b>                    | 202-715-5                          | 203-872-2                   |
| <b>CAS No.:</b>                   | 98-94-2                            | 111-46-6                    |
| <b>Substance content (% wt.):</b> | maximum 50.0                       | maximum 50.0                |

## GENERAL CHARACTERISTICS

| Parameter                    | Unit              | Requirements |
|------------------------------|-------------------|--------------|
| <b>Density at 20 °C</b>      | kg/m <sup>3</sup> | 973          |
| <b>Initial boiling point</b> | °C                | 162.3        |
| <b>Flash point</b>           | °C                | 56.5         |

## APPLICATIONS AREA

Used especially as **catalyst for polyurethane systems**, for production of surface materials, fillers of binding agents, sealing agents, softeners.

## SEGMENTS

- Polyurethane foam catalyst

## SYNONYMS

Ongrocat 6902

## HEALTH HAZARD EFFECTS

Toxic if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage.

## ADR REGULATIONS

UN 2920 CORROSIVE LIQUID, FLAMMABLE, n.o.s. IN,N-Dimethylcyclohexylamine, content 50 %, 8, II, (E)

## PACKAGING

Road tank cars  
Drums (216 l) 195 kg  
IBC (1,000 l) 910 kg